



Essential SmartBright Solar Flood Light

BVC080 LED15/765

Solar flood lighting DIY kit with lithium ferro phosphate battery built in the luminaire, Remote controller and installation accessories included. IP 65 ABS plastic construction for sturdiness and long life. Available in 600, 900 and 1500 Lumens

Warnings and Safety

- This product includes rechargeable batteries which must be adequately charged under sunlight before use.

Product data

General Information		Charge controller type		PWM			
Driver included	Yes						
Warranty period	1 years						
Light Technical		Temperature					
Luminous Flux	1,500 lm	Ambient temperature range				0 to +45 °C	
Correlated Color Temperature (Nom)	6500 K	Controls and Dimming					
Luminous Efficacy (rated) (Nom)	150 lm/W	Dimmable				Yes	
Color rendering index (CRI)	>70	Configurability				Configurable	
Optical cover type	Polycarbonate	Control interface				IR remote	
Operating and Electrical		Mechanical and Housing					
Battery type	Lithium Ferro Phosphate	Overall length				220 mm	
Battery ampere hour	10 Ah	Overall width				53 mm	
Battery voltage	3.2 V	Overall height				170 mm	
Panel type	Poly crystalline	Dimensions (Height x Width x Depth)				170 x 53 x 220 mm	
Panel voltage	5 V	Material				Acrylonitrile-butadiene-styrene	
Panel peak wattage	10 W						

Essential SmartBright Solar Flood Light

Approval and Application

Ingress protection code IP65 [Dust penetration-protected, jet-proof]

Application Conditions

Solar dimming profile As per remote controller

Battery location Inside luminaire

Product Data

Order product name BVC080 LED15/765

Full product name BVC080 LED15/765

Full product code 692382864896199

Order code 911401827402

Material Nr. (12NC) 911401827402

Numerator - Quantity Per Pack 1

EAN/UPC - Product/Case 6923828648961

Numerator - Packs per outer box 5

EAN/UPC - Case 6923828648817

Dimensional drawing

